10-4-00

COMMISSION PATENTS, Washington, D.C. 20231

Enclosed for filing is the patent application of Inventor(s):

GODWIN DIRK ZWANENBURG

For: DEVICE FOR REGENERATING AN ION EXCHANGE CARTRIDGE

ENCLOSED ARE:

Associate Power of Attorney;

Information Disclosure Statement, Form PTO-1449 and copies of documents listed therein;

Preliminary Amendment;

Specification (7 Pages of Specification, Claims, & Abstract);

Declaration and Power of Attorney:

(1 Page of a []fully executed [X]unsigned Declaration);

Drawing (3 sheets of []informal [X]formal sheets); Certified copy of EUROPEAN application Serial No. 99203248.2;

Authorization Pursuant to 37 CFR 1.136(a)(3);

Other: Citation of Related Cases;

Assignment to

FEE COMPUTATION

	1	CLAIMS AS	FILED	
FOR	NUMBER FILED	NUMBER EXTRA	RATE	BASIC FEE - \$710.00
Total Claims	8 - 20 =	0	X \$18 =	0.00
Independent Claims	1 - 3 =	0	X \$80 =	0.00
Multiple Depende	0.00			
TOTAL FILING FE	\$710.00			

Please charge Deposit Account No. 14-1270 in the amount of the total filing fee indicated above, plus any deficiencies. The Commissioner is also hereby authorized to charge any other fees which may be required, except the issue fee, or credit any overpayment to Account No. 14-1270.

Attorney

(914) 333-9640

CERTIFICATE OF MAILING

Express Mail Mailing Label No EL458218435US

Date of Deposit October 3, 2000

I hereby certify that this paper and fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1 10 on the date indicated above and is addressed to the Commissioner for Patents, Washington, D.C 20231


Elissa DeLuccy

Name

Send correspondence and papers to Corporate Patent Counsel U.S. Philips Corporation, 580 White Plains Road, Tarrytown, New York 10591

F:\WPDOCS\BT\N17665.forms.doc

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE



Atty. Docket

GODWIN DIRK ZWANENBURG

PHN 17,665

Filed: CONCURRENTLY

DEVICE FOR REGENERATING AN ION EXCHANGE CARTRIDGE

Commissioner for Patents, Washington, D.C. 20231

AUTHORIZATION PURSUANT TO 37 CFR §1.136(a)(3) AND TO CHARGE DEPOSIT ACCOUNT

Sir:

The Commissioner is hereby requested and authorized to treat any concurrent or future reply in this application requiring a petition for extension of time for its timely submission, as incorporating a petition for extension of time for the appropriate length of time.


Please charge any additional fees which may now or in the future be required in this application, including extension of time fees, but excluding the issue fee unless explicitly requested to do so, and credit any overpayment, to Deposit Account No. 14-1270.

Respectfully submitted,

Efrestine C. Bartlett, #22,861

Attorney

(914) 333-9640



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Atty. Docket

GODWIN DIRK ZWANENBURG

PHN 17,665

Filed: CONCURRENTLY

DEVICE FOR REGENERATING AN ION EXCHANGE CARTRIDGE

Commissioner for Patents, Washington, D.C. 20231

PRELIMINARY AMENDMENT

Sir:

Prior to calculation of the filing fee and examination, please amend the above-identified application as follows:

IN THE SPECIFICATION

Page 1, before line 1, insert the following heading:

--BACKGROUND OF THE INVENTION--;

Page 1, before line 17, insert the following heading:

--SUMMARY OF THE INVENTION--;

Page 2, before line 33, insert the following heading:

--BRIEF DESCRIPTION OF THE DRAWINGS--;

Page 3, before line 7, insert the following heading:

--DESCRIPTION OF THE PREFERRED EMBODIMENTS--.

IN THE CLAIMS

Please amend the claims as follows:

Claim 3, line 1, delete "or 2".

Claim 5, line 1, delete "or 4".

IN THE ABSTRACT

Page 7, before line 1, delete in its entirety and substitute the
following heading: --ABSTRACT OF THE DISCLOSURE--;

line 14, delete "Fig. 2".

REMARKS

This Preliminary Amendment is submitted to place the application in proper U.S. format. Entry is respectfully requested.

Respectfully submitted,

Ernestine C. Bartlett, #22,861

Attorney

(914) 333-9640

10

15

20

25

Device for regenerating an ion exchange cartridge.

The invention relates to a device for regenerating an ion exchange cartridge which is provided with an inlet and an outlet.

Tap water is heated in domestic appliances such as steam irons, coffee makers and electric kettles. A quantity of CaCO₃ and MgCO₃ is deposited in the heating process, depending on the hardness of the water. The deposit thus formed is referred to as scale. A scale deposit gives rise to inter alia an impaired heat transfer and choking-up of water duct systems, and in the end to a premature failure of the domestic appliance. To counteract scale depositions, it is known, for example in electric irons, to use so-called anti-scale cassettes or cartridges. Such cartridges usually contain a resin which binds the alkaline earth metal ions among them Ca²⁺ and Mg²⁺, but also, for example, CO₃²⁻, when coming in to contact with the water, so that no scale is formed. These cartridges are to be replaced with fresh cartridges from time to time, depending on the hardness of the water.

It is an object of the invention to provide a device with which the user of the domestic appliance him/herself can regenerate the cassette or cartridge in a simple manner, i.e. with which the alkaline earth metal ions can be removed from the cartridge, so that the cartridge can be re-used and need not be discarded.

The device according to the invention is for this purpose characterized in that the device is provided with a reservoir for the accommodation of a solution in which alkali metal ions and chloride ions are present, which reservoir is provided with an outlet to which the inlet of the ion exchange cartridge can be connected. The user takes the ion exchange cartridge from the domestic appliance and connects it with its inlet to the outlet of the reservoir of the regeneration device. Then the reservoir is filled with a solution in which alkali metal ions and chloride ions are present. After the reservoir has been filled, the solution

10

15

20

25

30

(or brine) flows into the ion exchange cartridge, with the result that the alkaline earth metal ions from the resin of the ion exchange cartridge are replaced by the alkali metal ions of the solution. Such a solution may consist, for example, of water in which a quantity of ordinary salt (NaCl) has been dissolved. The required quantity of salt, equal to the product of the volume (L) and the concentration (g/L), must be sufficient. This obviously depends on the size of the cartridge. The solution flowing from the cartridge and the reservoir may be caught, for example, in a kitchen sink. The regeneration device is a comparatively simple tool by means of which a user him/herself can make the cartridge ready for use again. Any (bi)carbonate and sulfate (possibly sulfite) ions present in the ion exchange cartridge, such as CO_3^{2-} or HCO_3^{-} and SO_4^{2-} or SO_3^{2-} , are exchanged with the Cl⁻ ions from the salt solution at the same time. It may be noted that the regeneration process is known per se from industrial applications.

2

A preferred embodiment of the device is characterized in that the device is provided with a chamber in which the ion exchange cartridge can be placed, which chamber is provided with an inlet and an outlet, said inlet of the chamber being connected to the outlet of the reservoir, while said inlet and outlet of the chamber are coupled to the inlet and outlet, respectively, of the cartridge when a cartridge is inserted. The chamber facilitates the placement of the cartridge in the device.

A further preferred embodiment of the device is characterized in that a restriction is present in the flow path of the solution situated between the outlet of the reservoir and the outlet of the chamber. The flow velocity of the solution through the cartridge can be adjusted thereby such that an optimum regeneration rate is obtained. The restriction may be, for example, a spring-loaded non-return valve.

A yet further embodiment is characterized in that the outlet of the reservoir lies at a higher level than the outlet of the chamber in the operational condition of the device. The reservoir will empty itself completely under the influence of the hydrostatic pressure.

In yet another embodiment, a filter is present in the flow path of the solution situated between the outlet of the reservoir and the inlet of the chamber. This prevents any impurities, which could adversely affect the operation of the ion exchange cartridge, from entering this cartridge.

The invention will now be explained in more detail below with reference to an embodiment shown in a drawing, in which

Fig. 1 is a perspective view of the device according to the invention,

Fig. 2 is a cross-section taken on the line II-II of the device of Fig. 1,

Fig. 3 is a cross-section taken on the line III-III of the device of Fig. 1, and

Fig. 4 is a cross-sectional view of the ion exchange cartridge.

5

10

15

20

25

30

As is apparent from the Figures, the regeneration device comprises a housing 1 which is substantially formed by a reservoir 2. The housing further has a chamber 3 whose upper side 4 is open. The bottom 5 of the chamber has an inlet 6 (Fig. 2) and an outlet 7 (Fig. 3). The bottom 8 of the reservoir 2 has a recessed portion 9 in which an outlet 10 is present. A filter 11 may be provided in the recessed portion 9. The outlet 10 is connected to the inlet 6 of the chamber 3, for example by means of a connecting tube 12, if necessary by means of a coupling piece 13. The outlet 7 of the chamber 3 may be provided with a discharge tube 14, possibly by means of a coupling piece 15. An ion exchange cartridge 16 has a housing 17 which is closed by a cover 18 at its upper side. The bottom 19 (see Fig. 4) of the housing 17 is provided with an inlet 20 and an outlet 21. The outlet 21 has a pipe 22 which stands up vertically in the housing 17 to just under the cover 18. The cartridge contains a resin 23. The ion exchange cartridge 16 can be placed in the chamber 3 of the device, such that the inlet 20 and the outlet 21 of the cartridge automatically connect to the inlet 6 and the outlet 7, respectively, of the chamber 3, possibly with the aid of respective sealing rings 24 and 25.

The operation of the regeneration device is explained below. When the ion exchange cartridge 16 appears to be saturated, i.e. the resin has absorbed so many alkaline earth metal ions that the water in the domestic appliance can no longer be adequately descaled, the cartridge is taken from the domestic appliance and placed in the chamber 3 of the regeneration device. The device is placed near the edge of the kitchen sink such that the discharge tube 14 is suspended in the sink. The reservoir 2 is then filled with ordinary tap water in which a quantity of kitchen salt (NaCl) has been dissolved. One liter of water with 10% by weight of NaCl is sufficient for most cartridges. The salt solution 26 will flow from the reservoir 2 through the filter 11 and the tube 12 to the resin 23 in the cartridge 16, and from there through the discharge tube 14 into the sink under the influence of gravity. The alkaline earth metal ions such as Ca²⁺ and Mg²⁺ ions, are replaced with Na⁺ ions from the salt solution in the resin. At the same time, the CO₃²⁻ (HCO₃⁻) and SO₄²⁻ (SO₃²⁻) ions are replaced with Cl⁻ ions from the salt solution. After the cartridge has been flushed with the salt solution, it can be returned to the domestic appliance again (for example, an electric iron). The flow of

5

the salt solution may be limited, or possibly controlled, by a restriction, for example a spring-loaded valve 27. A filter 11 at the outlet 10 of the reservoir 2 prevents any impurities from entering the cartridge 16. The outlet 10 of the reservoir 2 lies at a higher level than the outlet 7 of the chamber 3. The result of this is that the entire contents of the reservoir 2 will flow through the cartridge under the influence of the hydrostatic pressure. The pipe 22 in the cartridge 16 ensures that all resin 23 in the cartridge is effectively flushed with the salt solution 26.

10

15

25

CLAIMS:

- 1. A device for regenerating an ion exchange cartridge (16) which is provided with an inlet (20) and an outlet (21), characterized in that the device is provided with a reservoir (2) for the accommodation of a solution (26) in which alkali metal ions and chloride ions are present, which reservoir is provided with an outlet (10) to which the inlet (20) of the ion exchange cartridge (16) can be connected.
- 2. A device as claimed in claim 1, characterized in that the device is provided with a chamber (3) in which the ion exchange cartridge (16) can be placed, which chamber is provided with an inlet (6) and an outlet (7), said inlet (6) of the chamber being connected to the outlet (10) of the reservoir, while said inlet (6) and outlet (7) of the chamber are coupled to the inlet (20) and outlet (21), respectively, of the cartridge when a cartridge is inserted.
- 3. A device as claimed in claim 1 or 2, characterized in that a restriction (27) is present in the flow path of the solution situated between the outlet (10) of the reservoir (2) and the outlet (7) of the chamber (3).
- 4. A device as claimed in claim 3, characterized in that the restriction (27) is present in the inlet (6) of the chamber (3).
- 20 5. A device as claimed in claim 3 or 4, characterized in that the restriction (27) is provided with a spring-loaded non-return valve.
 - 6. A device as claimed in claim 2, characterized in that the outlet (10) of the reservoir (2) lies at a higher level than the outlet (7) of the chamber (3) in the operational condition of the device.
 - 7. A device as claimed in claim 2, characterized in that a filter (11) is present in the flow path of the solution situated between the outlet (10) of the reservoir (2) and the inlet (6) of the chamber (3).

The state of the s

8. A device as claimed in claim 2, characterized in that the outlet (7) of the chamber (3) is provided with a discharge tube (14).

ABSTRACT:

The invention relates to a device for regenerating an ion exchange cartridge. In household appliances with an electric heating element for heating water, such as irons, coffee makers, and electric water kettles, deposition of scale is prevented by using an ion exchange cartridge (16) comprising a resin (23) which binds alkaline earth metal ions such as Ca²⁺ and Mg²⁺, but also negative ions such as SO₄²⁻ and CO₃²⁻ ions. The device is a simple tool in which the cartridge can be inserted for regeneration. The device comprises a reservoir (2) with an outlet (10) to which an inlet (6) of the cartridge can be coupled. By filling the reservoir with a brine, for example 1 l of water with 10% by weight of NaCl, said brine will flow through the cartridge replacing the alkaline earth metal ions, carbonate ions, and sulfate ions in the resin with the alkali metal ions (Na⁺) and the chloride ions (Cl⁻) of the brine. The brine can be easily drained into a sink.

Fig. 2

And the body of the following the following

5

10




FIG. 1




FIG. 2





FIG. 3



DECLARATION and POWER OF ATTORNEY

ATTORNEY'S DOCKET NO .:

						PHN 17.665	
My residence, post of I believe I am the orig listed below) of the sub "Device for regenerat the specification of white I is attached hereto."	ject matter which is clai ing an ion exchange c ch (check one)	nship are as s ntor (if only or med and for v artridge"	ne name is li which a pate	sted below) or an origin	ention entitled		
the amendment(s) refer I acknowledge the du Federal Regulations, § I hereby claim foreign	rred to above. ty to disclose information 1.56(a). In priority benefits under and have also identified nich priority is claimed:	on which is ma	aterial to par	entability of this applicated	ition in accorda	(if applicable). ing the claims, as amended by ance with Title 37, Code of s) for patent or inventor's a having a filing date before that	
COUNTRY	UNTRY APP. NUMBER		DATE OF FILING		PRIORITY CLAIMED		
Europe 9	99203248.2		DATE, MON		UNDER 35 U.S.C. 119 YES		
Luiope	33200240.Z		COLODO			120	
first paragraph of Title 3 Federal Regulations, § of this application:	35 United States Code,	§112, I acknow between the f	owledge the filing date of	duty to disclose materia	al information and the national	the manner provided by the as defined in Title 37, Code of or PCT international filing date	
APPLICATION SERIAL NUMBER		FILING DATE		STATUS (PATENTED, PENDING, ABANDONED)			
believed to be true; and punishable by fine or in may jeopardize the validation of the power of	d further that these state of prisonment, or both, undity of the application of the Patent and Tradem of 26,902	ements were inder Section rany patent is	made with the sound of Title issued there oppoint the fo	ne knowledge that willfured the United States on. Ilowing attorney(s) and/	I false stateme s Code and that or agent(s) to	de on information and belief are ents and the like so made are at such willful false statements prosecute this application and aber)	
Edward M. Blocker, Re	g. No. 30,245	stant Course	al.	DIRECT TELEBUONE	CALLETO		
SEND CORRESPOND	•		ÇI,	DIRECT TELEPHONE CALLS TO: (name and telephone No.)			
U.S. Philips Corporation; 580 white Plains Road; Tarrytown, NY 10591			(914) 332-0222		·····		
Dated: Inventor's Signature: Full Name of in Last Name First Name Middle Name							
Inventor	ZWANENBURG		Godwin Dirk				

State of Foreign Country
The Netherlands

5656 AA Eindhoven

City

Country of Citizenship
The Netherlands

Zip Code

State of Country
The Netherlands

Residence &

Post Office Address

Citizenship

City Eindhoven

Street

Prof. Holstlaan 6

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE In re Application of Atty. Docket

GODWIN DIRK ZWANENBURG

PHN 17,665

Filed: CONCURRENTLY

DEVICE FOR REGENERATING AN ION EXCHANGE CARTRIDGE

Commissioner for Patents, Washington, D.C. 20231

APPOINTMENT OF ASSOCIATES

Sir:

The undersigned Attorney of Record hereby revokes all prior appointments (if any) of Associate Attorney(s) or Agent(s) in the above-captioned case and appoints:

ERNESTINE C. BARTLETT

(Registration No. 22,861)

c/o U.S. PHILIPS CORPORATION, Intellectual Property Department, 580 White Plains Road, Tarrytown, New York 10591, his Associate Attorney(s)/Agent(s) with all the usual powers to prosecute the above-identified application and any division or continuation thereof, to make alterations and amendments therein, and to transact all business in the Patent and Trademark Office connected therewith.

ALL CORRESPONDENCE CONCERNING THIS APPLICATION AND THE LETTERS PATENT WHEN GRANTED SHOULD BE ADDRESSED TO THE UNDERSIGNED ATTORNEY OF RECORD.

Respectfully,

Michael E. Marion, Reg. 32,266

Attorney of Record

Dated at Tarrytown, New York on October 2, 2000.